

ORDERING INFORMATION & PACKAGE DIMENSIONS OF C-CAP

瓷介電容訂貨指南及封裝尺寸

● Part Numbering System

CC	06	CH	50V	120	K	5C	
CC-T.C. CT.H.K. SC-Class III	Max. Diameter	Temperature Coefficient	Rated Voltage (V)	Nominal Capacitance 103=10,000pF	Tol	Lead Style	Lead Spacing
	04-4.5	NPO	-12		J-±5%	1	A-1 (2.5)
	05-5.5	N150	-16		K-±10%	2	B-2
	06-6.5	N470	-25		M-±20%	3	(5.0)
	10-10.5	N750	-50		Z-+80-20% (G.M.V.)	4	C-25
	12-12.5	SL(GP)	-100		P-+100-0%	5	(6.35)
	14-14.5	N1500	-250		C-±0.25pF		D-37
	16-16.5	N2200	-500		D-±0.5pF		(9.5)
		N3300	-1KV		F-±1pF		E-.03
		Y5F	-2KV				(7.6)
		Y5P	-3KV				
		Y5U					
		Y5R					
		Y5V					
		Y5T					
		Z5U					
		Z5V					

● Nominal Capacitance

	1	0	3	Significant Figure	Multiplier
First Significant Figure (Numeric)				0	0=X1
Second Significant Figure (Numeric)				1	1=X10
Multiplier (Numeric)				2	2=X10 ²
				3	3=X10 ³
				4	4=X10 ⁴
				5	5=X10 ⁵
				8	8=X10 ⁻²
				9	9=X10 ⁻¹

● Style & Dimensions

